



EC-70-LUXT

Digital DLP®-Rearprojection Cube

The new eyevis **EC-70-LUXT** is a modular rear-projection cube with a screen diagonal of 70" and **UXGA resolution (1,600 x1,200 pixels)**. The EC-70-LUXT uses innovative LED technology for illumination. EC-70-LUXT is a revolutionary development by eyevis and is completely produced in Germany. It is especially designed for applications which require a reliable 24/7 operation. The display technology is based on the DLP® technology (Digital Light Processing) by TEXAS INSTRUMENTS. This superior technology produces high-definition images of the highest quality. Whether you want to display video data or more complex graphics – you will always get a pin sharp image.

eyevis attached much importance on the possibility to use their cubes even in critical ambient light conditions or other challenging safety-related problems. The LUXT version uses a 1-chip-DLP® projector with a display resolution of 1,600 x 1,200 pixels. The MTBF of the LED lights lamps is indicated by the manufacturer with >60,000 hours. Thanks to the use of LED light technology, wear parts, such as colour wheels and traditional lamps are no longer necessary. The use of the DLP® technology guarantees that there is no damage to the display, such as "ghost"-images or burn-in effects, even with continuous static images or fixed patterns.

In numerous tests and comparisons the DLP® technology turned out to be the most reliable for continuous operation. The lieftime of the DMD™ chips is about 150,000 hours (MTBF: 650,000 hours). Of course, all the other parts of the device share the same high standards. This results in low service and maintenance costs for our customers.

The EC-70-LUXT has a screen size of 1400 mm width and 1050 mm height and is available with a standard "seamless" frame (0,3 mm). Furthermore, many optimising options, guarantee stable image quality of all cubes for a long period of time through automatic adjustment of values for brightness, contrast and colour.

Therefore the new eyevis EC-series allows realising completely flexible display walls, providing the highest colour fidelity, a maximum of brilliance and outstanding reliability. Optionally, there is an additional scaler board available with additional input possibilities and further enhancing features.



) ADVANTAGES OF EYEVIS EC CUBES

Outstanding picture quality

- High contrast and best brightness
- · Colour uniformity and wide viewing angle
- · Latest DLP® technology
- Best visibility in any lighting condition

Integrated optimising options

- Perfect system adjustment with eyeCube software
- · Fast and easy parameter setting
- Many status information available
- Optional Multi-Cube Colour-Brightness Adjustment

Availability and reliability

- Extremely long lifetime of the LED lights
- Qualitative high value components
- Especially designed for continuous operation
- · Highly efficient maintenance-free heatpipe cooling

Durability

- Durable and constant picture quality on all Cubes
- Modular, highly available display concept for 24/7 operation
- Low service and maintenance costs
- No wear parts as with traditional lamp systems

Ergonomics

- Very low noise level
- No rainbow effects and other DLP-typical artefacts
- Flexible image quality, adjustable parameters
- Completely dust-proof housing

Precision screen concept

- Perfect viewing angle
- · Minimum gaps between cubes thanks to clipping method
- Very easy and fast installation

) EC-70-LUXT





Digital DLP®-Rearprojection Cube

) ADVANTAGES COMPARED TO STANDARD LAMP/COLOUR WHEEL SYSTEMS

-) Shorter turning-on and start-up sequence compared to conventional lamp systems.
-) Real flicker-free representation without rainbow effects and therefore a more ergonomic and fatigue-free observation.
-) Higher lifetime with low tear and wear effects, no common wear parts like lamps and colour wheels as with traditional systems.
-) Much lower colour and brightness drifts over the life-time of the system, compared with traditional lamp systems.
-) High light output and higher lifetime through special colour-interleave method.
-) Improved representation of moving images.
-) Higher attention to detail, through a better colour gamut and colour space depth.

) TECHNICAL SPECIFICATIONS

Type:	EC-70-LUXT, eyevisCube 70" with LED illumination and native UXGA resolution
Description:	Digital 70" DLP®-rear- projection unit, stackable and addible, for data and video representation
Resolution:	1,600 x 1,200 Pixel (UXGA)
Processing:	Texas Instruments DMD-Chip (MTBF: approx. 650,000 hrs according to TI)
Brightness:	typ. 164 cd/m² (max. 205 cd/m²)
Contrast Ratio:	1,500:1 (max. 5,000:1 dynamic contrast)
Brightness Uniformity:	≥95%
Image Size (WxH):	1400 x 1050 mm (ca. 70" screen diagonal)
Dimensions (WxHxD):	1400 x 1270 x 750 mm
Weight:	ca. 95 kg
Input:	1x DVI-D, optional with Scaler Board: 2x RGB, 2x DVI, 2x Composite Video, 1x Y/C, 1xYUV, 1x S-Video
Projection Screen:	Seamless CrossPrism Screen, viewing angle horizontal & vertical 180° (different screens on request)
Frame:	0.3 mm
Power Consumption:	250 Watt (typ.) at 110/240 VAC
Heat Dissipation:	853 BTU/h (typ.)
Median LED Lifetime:	>60,000 hrs under normal environmental conditions / L70B50 manufacturer information) (75,000 - 90,000 hrs in 'Low Power Operation Mode', i.e. additional 15,000 to 30,000 hrs depending on the amount of power reduction)
Software:	eyevisCubeManager

) Environmental:

Temperature Conditions:	10-40° C / recommended 15 - 25 °C / for Seamless Screens 18 - 25 °C / Storage: 0 - 50 °C
Humidity:	0% - 80 % not condensating
Altitude:	0 - 3000 m
Noise Level:	≤36dB

) Options:

- Scaler Board (internal split controller up to 10x10 Matrix, with 2x DVI, 2x RGB, 2x Video)
- · ACT Auto-Colour Tracking, auto-adjustment of brightness and colours for each display according to the adjusted values
- EYE-MSP Matrix-Shading-Processor integrated in cube
- EYE-SCP Shading and Colour Processor integrated in cube
- EC-MAS motorized geometry adjustment via IR remote control or PS2 $\,$
- · Network Board
- Service and Maintenance Contracts
- Different Basement Options: Standard Basement, Basements on Wheels, Basements on Rails, Anti-Vibration Basements



eyevis GmbH

Hundsschleestrasse 23 · 72766 Reutlingen · Germany Phone: + 49 (0) 7121 43303 - 0 · Fax: + 49 (0) 7121 43303 - 22 www.eyevis.de · info@eyevis.de As at: 01.08.2012/V1.2 · Subject to change! All trademarks and registered trademarks are the property of their respective owners. Copyright © 2011 eyevis GmbH. All rights reserved.