

# ) EYE-LCD-2200-TP-CO

eyevis Transparent LCD Series

## ) DESCRIPTION

With the new LCD display EYE-2200-TP-CO eyevis presents an innovative new development in the LCD field. As the name suggests, the transparency of the panel is so revolutionary about this new display type. This makes it ideally suited for integration in shop windows, trade stands and other areas where the impression of the viewer should be obtained. In a unique way, it is possible with these new display types to combine displayed information and graphics with a real object in the background.

## ) FEATURES

- ) 22" screen diagonal
- ) WSXGA+ resolution
- ) high light transmission
- ) very fast response times
- ) device includes only panel and LCD driver, an external backlight is required which can be integrated for example in a display case.
- ) suitable for using in portrait and landscape format

## ) TECHNICAL SPECIFICATIONS

### ) LC Display

Type	<b>EYE-LCD-2200-TP-CO</b>
Paneltype	22" E-DID (ca. 55cm)
Display-Resolution	1.680 x 1050px (WSXGA+)
Contrast Ratio	500:1
Frequency	60Hz
Aspect Ratio	16:10
Transmittance	15% /typ.)
Viewing Angle	± 160° H/V
Panelinterface	LVDS
Control	HDMI

### ) Mechanical

Dimensions (WxHxD)	493,7 x 371,0 x 22,0 mm
Frames (le./ri./t./b.)	8 / 8 / 10 / 61 mm
Weight:	1,3 kg
Frame Colour:	black

### ) Environmental

Power Consumption	7.2 Watt
Operation	Temperature: 20°C ± 15°C Humidity: 55 ± 20% Display: moving picture or regular switchover display (long-term static information image may cause uneven display)
Storage	-25 – 60 °C

## ) APPLICATION POSSIBILITIES

- ) showcases / display cases, e.g. in museums
- ) product presentation / POS display
- ) interior, e.g. installation in doors
- ) sales areas / information areas
- ) fairs / events
- ) touch tables

## ) IMAGES



Application possibility with model car in show case

## ) DRAWING

