



EYE-LCD-8200-HDMI-LB (Lower Brightness)

eyevis LCD Series

DISPLAY CHARACTERISTICS

-) Professional 82 inch LCD-Monitor with S-PVA TFT-Display Panel
-) Full HD Resolution (1920x1080px)
-) 16:9 Aspect Ratio / Landscape or Portrait Installation
-) Metal Standard Chassis (standard black RAL9005, different RAL colours available on request)
-) Various Input Possibilities
-) Best LCD Quality at an unbeatable Price
-) Different Installation Possibilities
-) Optionally available with High Quality Speakers

TECHNICAL SPECIFICATIONS

LCD Panel

Technology	S-PVA LCD
Max. Image Resolution	1,920 x 1,080 (full HD)
Colours	16.7M (8bits-true)
Viewing Angle	178° / 178° (H/V)
Response Time	8 ms (Grey-to-Grey)
Contrast Ratio	2000:1
Brightness	450 cd/m ² (Typical)

Connectors & Control

Inputs	1 x Display Port, 2x HDMI 1.3, 1x RGB (15-pin H-DSUB female), 1x Video
Outputs	1 x DVI-D

Power Supply

Input Voltage	100-250V 50/60Hz; Integrated Mains Adapter
Power Consumption	950 Watt (max. 1400 Watt)

Environmental

Temperature	0-40°C (<50%RH)
Humidity	20-80%RH (T<40°C)

Mechanical

Screen Diagonal	82" (ca. 208 cm)
Screen Area	1808 x 1016 mm
Dimensions (WxHxD)	1926 x 1137 x 150 mm
Bezel	top/bottom 60.5 mm, right/left 59 mm
Weight	110 kg

Options

Input Option:	1 x Display Port up to 2560x1600 (60Hz), HDCP support 2 x HDMI 1.3, True High Definition 1080p, HDCP support 1 x RGB (15-pin H-DSUB female), captures up to 205MHz, Supports up to 1792x1344@60Hz or 1920x1260@60Hz or 1600x1200@75Hz standard modes 1 x Video Input, supports Composite Video, S-Video, and Component Video 1 x 3G-HD-SDI input (optional) 1 x RS232 Serial Port 1 x Audio In (L/R Cinch)
Audio:	High Quality Speakers + integr. Amplifier
Touch:	Optical Touch Surface
Installations:	Different Wallmounts and Stands available



eyevis GmbH
 Hundsschleestr. 23 • 72766 Reutlingen • Germany
 Phone: + 49 (0) 7121 43303 - 0 • Fax: + 49 (0) 7121 43303 - 22
 www.eyevis.de • info@eyevis.de
 As at: 13.07.2012 / V1.1 • Subject to change!
 All trademarks and registered trademarks are the property of their respective owners. Copyright © 2011 eyevis GmbH. All rights reserved.